

High-visibility safety apparel – unraveled

OAR 437
Division 2/I
Division 3/E

High-visibility safety apparel
– unraveled

If you work in a street or highway right-of-way and you're exposed to traffic or construction equipment, you must wear a highly visible upper-body garment in accordance with *High visibility garments* (437-002-0134(7) or 437-003-0134(7), the requirements are identical). Emergency responders and law enforcement officers must also wear high-visibility apparel *after* an emergency has passed and they're doing traffic control, cleanup, investigations, or similar tasks.

Does a worker changing a tire, or a delivery truck driver who is making a delivery, need to wear a high-visibility upper body garment? Either one of these workers may be required to wear high-visibility apparel, depending on their exposure; they may be able to eliminate the exposure during the course of their work.

High-visibility apparel is usually not required for workers such as parking lot attendants and warehouse workers who do not have street or highway exposure; however, wearing the garment makes them more visible. Employers should assess their employees' risk of exposure and make the determination.

What to wear

When you must wear a high-visibility upper-body garment, Oregon OSHA rules require that the colors of the vest (such as strong red, orange, yellow, and yellow-green) must contrast with other colors in the area sufficiently to make you stand out. The garments must also reflect from all sides for 1,000 feet, during hours of darkness.

Most employers whose employees are exposed to vehicle traffic follow **The American National Standard for High-Visibility Safety Apparel and Headwear**, (ANSI/ISEA 107-2010), which sets the performance criteria for high-visibility apparel. This safety apparel consists of *background material*, *retroreflective material*, and *combined-performance material*:

Background material is "colored fluorescent material intended to be highly conspicuous, but not intended to comply with the requirements... for retro-reflective material."

Retroreflective material is "material that reflects and returns a relatively high proportion of light in a direction close to the direction from which it came."

Combined-performance material is "retroreflective material that is also a fluorescent material and can be counted toward the minimum area requirements for background material."

XYZ Manufacturer
ANSI/ISEA 107-2010
and ANSI/ISEA 107-2004
100% Polyester
3M™ Scotchlite™ Reflective Material
Model #: Hi Vis Vest
Size: Large



Class 2

Level 2

FR- ASTM F1506-08
Washing Instructions



Wash warm Max 25 cycles
Do not bleach
Tumble dry low
Do not iron
Do not dry-clean

Website:

www.orosha.org

Salem Central Office
350 Winter St. NE, Rm. 430
Salem, OR 97301-3882

Phone: 503-378-3272
Toll-free: 800-922-2689
Fax: 503-947-7461



ANSI/ISEA also has three numbered performance classifications for high visibility apparel:

Performance class 1

- Minimum background material: 217 in.²
- Minimum retroreflective material: 155 in.²
- Provides the minimum amount of required material to distinguish the wearer from the environment
- Intended for workers whose tasks don't divert their attention from approaching traffic
- Intended for locations where the worker is separated from traffic, which is traveling no faster than 25 mph

Performance class 2

- Minimum background material: 775 in.²
- Minimum retroreflective material: 201 in.²
- Provides enhanced visibility during inclement weather
- Intended for workers whose tasks divert their attention from approaching traffic and for those who must work near vehicles exceeding 25 mph

Performance class 3

- Minimum background material: 1240 in.²
- Minimum retroreflective material: 310 in.²
- Provides maximum visibility for workers who have tasks that place them in imminent danger from approaching traffic
- Provides maximum visibility when the wearer must be conspicuous at a minimum distance of 1,280 feet

ANSI/ISEA requires high-visibility apparel manufacturers to include specific information about their products on the inside label of each garment, including the performance classification number and a pictogram or drawing of the garment. **Read the label to make sure the garment is ANSI/ISEA 107-2010 compliant and that it meets your needs.**

The table below shows typical recommended performance apparel classifications for various types of jobs. To determine the appropriate apparel, always consider the environmental conditions where you'll be working and your risk of exposure.

Type of jobs	Performance classification		
	Class 1	Class 2	Class 3
shopping cart retrievers	■		
warehouse workers	■		
delivery truck drivers	■		
roadway construction workers		■	■
utility workers		■	■
surveyors		■	■
emergency responders		■	■
flaggers			■

Adapted from ANSI/ISEA 107-2010, Appendix B

More information

High-visibility garments, 437-002-0134(7) (general industry) and **437-003-0134(7)** (construction) – Oregon OSHA's key rules on high-visibility apparel. The requirements are identical.

American National Standard for High-Visibility Safety Apparel and Headwear, ANSI/ISEA 107-2010 – establishes the performance criteria for materials used in high-visibility apparel.

The American National Standard for High-Visibility Public Safety Vests, ANSI/ISEA 207-2006 – establishes the performance criteria for public safety vests used by emergency responders and law enforcement officers.

Manual on Uniform Traffic Control Devices (MUTCD) 2009 – The MUTCD sets national traffic control standards and refers to **ANSI/ISEA 107** and **ANSI/ISEA 207**. Relevant sections of the MUTCD include **Chapter 6D, Pedestrian and Worker safety**, and **Chapter 6E, Flagger Control**.