

PRODUCT SPECIFICATIONS FOR CB24B

WEIGHTS

Operating Weight	6003 lb
-------------------------	---------

Maximum Weight at Front Drum	2857 lb
-------------------------------------	---------

Maximum Weight at Rear Drum	3147 lb
------------------------------------	---------

OPERATING SPECIFICATIONS

Standard Compaction Width	47 in
----------------------------------	-------

Curb Clearance	20 in
-----------------------	-------

Turning Radius - Inside Drum Edge	8 ft
--	------

Ground Clearance	11 in
-------------------------	-------

Travel Speed - Maximum	7.5 mile/h
-------------------------------	------------

Static Linear Load	63 lb/in
---------------------------	----------

ENGINE

Gross Power	36.2 HP
--------------------	---------

Engine Model	C1.5
---------------------	------

DIMENSIONS

Overall Length	101 in
-----------------------	--------

Wheel Base	71 in
-------------------	-------

Overall Width	52 in
----------------------	-------

Maximum Machine Height	106 in
-------------------------------	--------

Drum Diameter	28 in
Drum Width	47 in

VIBRATORY SYSTEM

Centrifugal Force per Drum - Minimum	3282 lb
Centrifugal Force per Drum - Maximum	7374 lb
Nominal Amplitude - High	0.021 in
Frequency	63/55/42 Hz (3,780/3,300/2520 vpm)

SERVICE REFILL CAPACITIES

Fuel Tank Capacity	17 gal (US)
Water Spray Tank Capacity	62 gal (US)

CB24B OPTIONAL EQUIPMENT

ANTI-FREEZE SYSTEM

BALLAST

BATTERY DISCONNECT SWITCH

BIO-HYDRAULIC OIL

FOLDABLE CANOPY

FIXED CANOPY

DUAL PROPEL LEVERS

NON-SUSPENSION SEAT

PRODUCT LINK

FIXED ROPS

FOLDABLE ROPS

SEAT W/OPERATOR PRESENCE SWITCH

SLIDING SEAT

TRACTION CONTROL