

AERVOE-PACIFIC INC -- 17A MARKING PAINT-ALL COLORS 200 CLEAR

=====

MSDS Safety Information

=====

FSC: 8010
 MSDS Date: 08/19/1997
 MSDS Num: CGWFB
 LIIN: 00F056094
 Product ID: 17A MARKING PAINT-ALL COLORS 200 CLEAR
 MFN: 01
 Responsible Party
 Cage: 0UPL1
 Name: AERVOE-PACIFIC CO INC
 Address: 1198 SAWMILL RD
 City: GARDNERVILLE NV 89410-5000
 Info Phone Number: 702-782-0100/408-295-7390
 Emergency Phone Number: 408-295-7390/702-782-0100
 Preparer's Name: MIKE A TRAQUINA
 Published: Y

=====

Preparer Co. when other than Responsible Party Co.

=====

Cage: 0UPL1
 Name: AERVOE-PACIFIC CO INC
 Address: 1198 SAWMILL RD
 City: GARDNERVILLE NV 89410

=====

Contractor Summary

=====

Cage: 0UPL1
 Name: AERVOE-PACIFIC CO INC
 Address: 1198 SAWMILL RD
 City: GARDNERVILLE NV 89410
 Phone: 702-782-0100

=====

Ingredients

=====

Cas: 1330-20-7
 RTECS #: ZE2100000
 Name: XYLENE, DIMETHYLBENZENE, XYLOL (IARC - GROUP 3) *98-1*
 % Wt: 13
 Other REC Limits: 100 PPM
 OSHA PEL: 100 PPM
 ACGIH TLV: 100 PPM, SKIN
 EPA Rpt Qty: 1000 LBS
 DOT Rpt Qty: 1000 LBS

Cas: 64742-89-8
 Name: LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE *98-1*
 % Wt: 20
 OSHA PEL: 300 PPM
 ACGIH TLV: 300 PPM

Cas: 8052-41-3
 RTECS #: WJ8925000
 Name: STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL SPIRITS *98-1*
 % Wt: <5
 Other REC Limits: 525 MG/CUM
 OSHA PEL: 500 PPM
 ACGIH TLV: 100 PPM

 Cas: 74-98-6
 RTECS #: TX2275000
 Name: PROPANE (DIMETHYLMETHANE) *98-1*
 % Wt: 15
 Other REC Limits: 1800 MG/CUM
 OSHA PEL: 1000 PPM
 ACGIH TLV: SIMPLE ASPHYXIAN

Cas: 75-28-5
 RTECS #: TZ4300000
 Name: ISOBUTANE, 2-METHYLPROPANE
 % Wt: <5
 Other REC Limits: 1000 PPM
 OSHA PEL: 1800 MG/CUM
 ACGIH TLV: 1000 PPM

Cas: 106-97-8
 RTECS #: EJ4200000
 Name: BUTANE, N-BUTANE *98-1*
 % Wt: 5
 Other REC Limits: 800 PPM
 OSHA PEL: 800 PPM
 ACGIH TLV: 1900 MG/CUM
 =====

Health Hazards Data

=====

LD50 LC50 Mixture: ORAL LD50(RAT): 4300 MG/KG
 Route Of Entry Inds - Inhalation: YES
 Skin: NO
 Ingestion: YES
 Carcinogenicity Inds - NTP: NO
 IARC: NO
 OSHA: NO
 Effects of Exposure: SKIN: IRRITATION/DERMATITIS. EYES: IRRITATION. INHALATION:
 ANESTHETIC, IRRITATION OF THE RESPIRATORY TRACT/NERVOUS DEPRESSION.
 Explanation Of Carcinogenicity: NONE
 Signs And Symptions Of Overexposure: DIZZINESS, NAUSEA, IRRITATION, BURNING
 SENSATION, HEADACHE, NAUSEA, UNCONSCIOUSNESS.
 First Aid: INHALATION: REMOVE TO FRESH AIR & RESTORE BREATHING. SKIN: WASH
 AREA. EYES: FLUSH W/WATER FOR 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES.
 =====

Handling and Disposal

=====

Spill Release Procedures: REMOVE SOURCES OF IGNITION. VENTILATE AREA & SOAK
 UP W/INERT ABSORBENT USING NON-SPARKING TOOLS.
 Waste Disposal Methods: DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.
 DON'T INCINERATE CLOSED CONTAINERS. UN1950.
 Handling And Storage Precautions: DON'T STORE >120F. DON'T STORE/USE NEAR
 HEAT, SPARKS/FLAME.
 Other Precautions: DON'T GET IN EYES. DON'T BREATHE VAPORS. AVOID SKIN CONTACT.
 DON'T TAKE INTERNALLY. SMOKING IS PROHIBITED. DUST FROM SANDING THE DRY PAINT
 FILMS SHOULD BE TREATED AS A NUISANCE DUST W/A TLV OF 10MG/CM . AVOID
 PROLONGED/REPEATED CONTACT.
 =====

Fire and Explosion Hazard Information

=====

Flash Point Method: TCC
 Flash Point Text: -250F
 Lower Limits: 0.7

Upper Limits: 9.5

Extinguishing Media: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures: WATER SPRAY MAY BE INEFFECTIVE, BUT WATER SPRAY MAY BE USED TO COOL CONTAINERS EXPOSED TO HEAT/FIRE TO PREVENT PRESSURE BUILD UP.

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE DUE TO BUILDUP OF PRESSURE FROM EXTREME HEAT/FIRE.

Control Measures

Respiratory Protection: OUTDOORS, WE RECOMMEND AN APPROVED PARTICULITE FILTER TO REMOVE ANY AIRBORNE OVERSPRAY. IN RESTRICTED AREAS, A NIOSH APPROVED RESPIRATOR W/ORGANIC VAPOR CARTRIDGE IS RECOMMENDED.

Ventilation: ADEQUATELY: IN ORDER TO KEEP BELOW EXPOSURE LIMITS.

Protective Gloves: IMPERVIOUS/NATURAL RUBBER

Eye Protection: SAFETY GLASSES W/SIDE SHIELDS

Other Protective Equipment: IMPERVIOUS APRON, EYE WASH FOUNTAIN & SAFETY SHOWER.

Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Physical/Chemical Properties

B.P. Text: 100F

Vapor Density: >1

Spec Gravity: 0.8

VOC Pounds/Gallon: 4.7

Evaporation Rate & Reference: FASTER THAN N-BU AC

Solubility in Water: NEGLIGIBLE

Appearance and Odor: OPAQUE LIQUID W/SOLVENT ODOR

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: HIGH TEMPS.

Materials To Avoid: STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products: CO, CO2.

Hazardous Polymerization Indicator: NO

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

Other Information: VOLATILE ORGANIC CONTENT: 4.70 LBS/GAL

HAZCOM Label

Product ID: 17A MARKING PAINT-ALL COLORS 200 CLEAR

Cage: 0UPL1

Company Name: AERVOE-PACIFIC CO INC

Street: 1198 SAWMILL RD

City: GARDNERVILLE NV

Zipcode: 89410
Health Emergency Phone: 408-295-7390/702-782-0100
Label Required IND: Y
Date Of Label Review: 10/12/1999
Status Code: A
Origination Code: G
Hazard And Precautions: SKIN: IRRITATION/DERMATITIS. EYES: IRRITATION.
INHALATION: ANESTHETIC, IRRITATION OF THE RESPIRATORY TRACT/NERVOUS
DEPRESSION.

=====

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.